## MONTANA STATE AVIATION SYSTEM PLAN 1995 UPDATE FIELD INSPECTION FORM

AIRPORT:	STEVENSVILLE (32S)	AIRPORT REFERENCE CODE:	B-I (SM)
CITY:	STEVENSVILLE	APPROACH TYPE:	VISUAL
CONTACT:	DON MISEVIC	DATE INVENTORIED:	12-26-95
PHONE #:	777-2006	INSPECTED BY:	RSD

	REQUIRED		ACTUAL		ALP	1	CONFORM
RUNWAY 12/30 INVENTORY							
DISTANCE TO:							
HOLD LINES FROM CENTERLINE:	125'		115' - 197'				NO
PARALLEL TAXIWAY FROM CENTERLINE:	150'		240'				✓
AIRCRAFT PARKING FROM CENTERLINE:	125'				210'		<b>✓</b>
RUNWAY WIDTH:	60'		60'				1
RUNWAY LENGTH:	5,180 (1)				3,800'		75%
RUNWAY SAFETY AREA (RSA) WIDTH:	120'		OK		-,		1
RUNWAY OBJECT FREE AREA (OFA) WIDTH:	250'		OK				<b>✓</b>
PRIMARY / TRANSITION SURFACE PENETRATIONS:	250' W & 7:1		(2) & (3)				NO
LONGITUDINAL GRADE - SITE DIST. PROBLEMS:			OK				1
OBSTACLE FREE ZONE ANALYSIS:	250' W x 200' E	3F\	_				/
PAVEMENT EDGE LIP HEIGHT (MIN AND MAX):	1.5" - 3"		1.5"				1
PAVEMENT MARKING TYPE:	BASIC		BASIC				/
PAVEMENT MARKING CONDITION:	<i>B</i> , (6.6		FAIR/GOOD	(4)			N/A
TAVENERY WARRING CONDITION.			7.111.0000	( '/			14//
RUNWAY 12 END INVENTORY							
SAFETY AREA (RSA) BEYOND RUNWAY END:	240'		OK				✓
OBJECT FREE AREA (OFA) BEYOND RUNWAY END:	240'		OK				✓
APPROACH OBSTRUCTIONS:	20:1		NONE				✓
RUNWAY END ELEVATION:					3,535.0		N/A
RUNWAY 30 END INVENTORY							
SAFETY AREA (RSA) BEYOND RUNWAY END:	240'		ок				<b>✓</b>
OBJECT FREE AREA (OFA) BEYOND RUNWAY END:	240'		OK				/
APPROACH OBSTRUCTIONS:	20:1		NONE (5)				/
RUNWAY END ELEVATION:	20.1		INOINE (3)		3,609.5		N/A
NOWWIT END LEEVITION.					0,000.0		14// (
RUNWAY LIGHTING INVENTORY							
DISTANCE FROM PAVEMENT EDGE:	10'		10'				✓
MAXIMUM DISTANCE BETWEEN LIGHTS:	200'		OK				✓
TYPE:	MIRL - STAKE	MC		AL	.NACO		N/A
CONDITION:			GOOD				N/A
COLOR:	WHITE		WHITE				✓
THRESHOLD 12							
DISTANCE FROM PAVEMENT EDGE:	10'		7'				NO
MAXIMUM DISTANCE BETWEEN LIGHTS:	10'		10'				 ✓
COLOR:	RED/GREEN		RED/GREEN				1
							·
THRESHOLD 30	401		41 51				NO
MANUALIM DICTANICE DETWEEN LICUTO	10'		1' - 5'				NO
MAXIMUM DISTANCE BETWEEN LIGHTS:	10'		10'				/
COLOR:	RED/GREEN		RED/GREEN				✓

## COMMENTS:

- (1) RW LENGTH OF 3,780' FOR 75%, 4,800 FOR 95% AND 5,180 FOR 100% COVERAGE; ALP ULT OF 4,800' SHOWN ON ALP
- (2) TREES PENETRATE TRANSITIONAL SURFACE (16% 17%), OTHERS OUTSIDE PROPERTY LINE MAY

PENETRATE TRIANGULAR PORTION OF TRANSITIONAL SURFACE ADJACENT TO APPROACH SLOPE

- (3) LARGE COTTON WOOD TREES OUTSIDE PROPERTY LINE PENETRATE TRANSITIONAL SURFACE @  $\sim$ 29% 32% TREES ALONG FENCE LINE ALSO PENETRATE TRANSITIONAL SURFACE @ 29% 50%
- (4) RUNWAY END NUMBERS FRESHLY PAINTED, BUT RUNWAY STRIPE FADED
- (5) TREES ~1MI OUT ARE AT ABOUT 20:1

## MONTANA STATE AVIATION SYSTEM PLAN 1995 UPDATE FIELD INSPECTION FORM

FIELD INSPECTION FORM								
AIRPORT:	STEVENSVILLE (32S)		B-I (SM)					
CITY:	STEVENSVILLE	APPROACH TYPE:			VISUAL			
CONTACT:	DON MISEVIC	DATE INVENTORIED:			12-26-95			
PHONE #:	777-2006	INSPECTED BY:			RSD			
					_			
TAYIMAY INIMEN	ITORY	REQUIRED	ACTUAL	ALP	CONFORM			
TAXIWAY INVENTORY TAXIWAY WIDTH:		25'	30' & 35'		NO			
TAXIWAY SAFETY AREA WIDTH:		49	OK		/			
TAXIWAY OBJECT FREE AREA WIDTH:		89	OK		<b>✓</b>			
DIST. FROM CENTERLINE TO FIXED OR MOVEABLE OBJ.		44.5	OK		<b>/</b>			
PAVEMENT EDGE LIP HEIGHT (MIN AND MAX): PAVEMENT MARKING TYPE:		1.5" - 3"	FLUSH YELLOW		NO ✓			
	RKING CONDITION:		NEW		N/A			
I AVEIVIENT IVIAI	ANING CONDITION.		INE VV		IN/A			
TAXIWAY LIGHT	ING INVENTORY							
	M PAVEMENT EDGE:	10'	10'		✓			
	ANCE BETWEEN LIGHTS:	200'	OK		<b>√</b>			
TYPE:			REFLECTOR		N/A			
CONDITION: COLOR:		BLUE	GOOD BLUE		N/A			
COLOR.		BLUE	BLUE		/ /			
MISCELLANEOU	JS							
TYPE OF BEACO	ON:	MOUNTED ON :	35' WOOD POLE SE O	F APRON				
SIZE OF BEACC	N:	12"						
OTHER LIGHTING AIDS (VASI,PAPI,REIL):		12 END, ADB ALNACO PAPI, IN GOOD COND, 50' OFF PVMT						
WINDCONE (CONDITION & COMPLIANCE):		NORTH OF RW ~300', NEW COND, 20'+ HIGH						
SEGMENTED CIRCLE (CONDITION & COMPLIANCE):		METAL PANEL SEGMENTED CIRCLE IN GOOD COND						
WINDCONE (CC	NDITION & COMPLIANCE):							
SEGMENTED CI	RCLE (CONDITION & COMPLIANCE):							
FENCING:		GOOD						
SIGNS: (TYPE, C	CONDITION, PLACEMENT)	NEW LUMACUF	RVE, 15' FROM PVMT	EDGE 207' FROM	RW CL			
COMMENTS:								